308E CR MNI HYDRAULIC EXCAVATOR WITH SWING BOOM | 8T

PRODUCT SPECIFICATIONS

Weights	
Operating Weight - With cab	8,400 kg
NOTE: Weight includes rubber tracks, bucket, operator (75 kg Weight varies depending on machine configuration.	g/165 lb), full fuel and auxiliary lines.
Drive System	
Travel Speed - High	5.1 km/h / 3.17 mph
Travel Speed - Low	2.8 km/h / 1.74 mph
Maximum Traction Force - Low speed	37.4 kN
Maximum Traction Force - High speed	64.5 kN
Ground Pressure	36.3 kPA
Engine	
Model	CAT C3.3B
Rated Net Power	48.5 kW / 65 hp
Gross Power	49.7 kW / 66.6 hp
Bore	94 mm
Stroke	120 mm
Displacement	3.33 L
Swing system	
Machine Swing Speed	11 rpm
Boom Swing - Left	60°
Boom Swing - Right	50°
Automatic swing break, spring applied, hydraulic release.	
Blade	
Width	2,320 mm / 91.3"
Height	450 mm / 17.7"
Dig Depth	360 mm / 14.2"
Lift Height	380 mm / 15.0"
Fuel Burn	
Low	2.7 - 5.4 Litres per hour
Medium	5.4 - 8.0 Litres per hour
High	8.0 - 10.7 Litres per hour







