

5055F TRACTOR SLASHER

PRODUCT SPECIFICATIONS

JOHN DEERE

Model	
Engine	John Deere 2.9-litre, 3-cylinder, PowerTech M engine with turbocharger and charge air cooler
Number of Cylinders / Aspiration	3
Displacement (cm³)	2,900 (2.9L)
Emissions Level	U.S. EPA Tier 3
Fuel Tank Capacity (L)	68 (IOOS) 80 (CAB)
Performance	
Rated Power (97/68/EC), kW (hp)	40.5 (55)
Rated Power (ECE-R24)	38.1 (52)
Rated Speed (rpm)	2,400
Max. Torque (Nm)	214
Max. Torque @ Engine Speed (rpm)	1,300



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is: for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.