

BD3150 HDCC TRACTOR

PRODUCT SPECIFICATIONS

KUBOTA

Engine	
Type	E-TVCS, liquid cooled, 4-cylinder diesel
Make, Model	V1505-E3-D26BH-A
PTO horsepower	23.7 (17.7) HP (kW)
Engine gross horsepower*	31.0 (22.8) HP (kW)
Rated RPM	2,500 rpm
Bore and stroke	78 x 78.4 mm
Displacement	1,498 cc
Air cleaner	Double element
Lubrication	Forced lubrication
Cooling system	Pressurized radiator
Radiator fan	Radial air flow
Capacities	
Fuel tank	27 L
Cooling system	4.6 L
Engine oil	4.0 L
Transmission case	15 L
Drive train	
Clutch	N/A
Transmission	HST (3 ranges)
Differential lock	Standard
Final drive	Standard
Brake	Multi-plate wet disc
PTO	
Type	Independent
Rear	540 rpm
Mid	2,400 rpm
Hydraulics	
Type	Open center
Pump	Dual pump
Total pump output	33.1 L/min.
Hydraulic outlet	Rear outlet
3-point hitch	Category I
Hydraulic control system	Position control valve
Lift capacity (at lift point)	970 kg
Lift capacity (24" behind LP)	760 kg
Cruise control	STD
Steering	Hydraulic power steering



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is: for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.

ezyquiphire
Hire and Maintenance Specialists