

5055F TRACTOR SLASHER

PRODUCT SPECIFICATIONS

JOHN DEERE

Power Systems	
Engine Model	Briggs & Stratton 31R9 / Briggs & Stratton 33R8
Horsepower*	17.5 hp (13.0 kW) / 19.0 hp (14.2 kW)
Cylinders	One
Displacement	500 cc (30.5 cu in.) / 540 cc (33 cu in.)
Oil Filter	Traditional
Air Filter	Cartridge
Mower Deck	
Cut Width	107 cm (42 in.)
Cutting Blades	Two
Cut Height	25.4 to 102 mm (1 to 4 in.)
Mower Deck Material	Stamped steel
Blade Engagement / PTO	Manual
Transmission	
Type	Hydrostatic
Turning Radius	
	46 cm (18 in.)
Electrical System	
Capacity	8 amp
Fuel System	
Fuel Gauge	Mechanical
Fuel Tank Capacity	9.08 L
Type of Fuel	Petrol
Fuel Filter	Replaceable, in fuel line
Travel Speed	
Forward	8.9 km/h (0-5.5 mph)
Reverse	4.8 km/h (0-3.0 mph)
Seat	
Height	27.9 cm (11 in.) / 38.1 cm (15 in.) one piece / open back
Tyres	
Front	15x6-6
Rear	20x8-8
Dimensions	
Overall Length	175 cm (42.5 in.)
Overall Width (deflector down)	140 cm (55.2 in.)
Height	108 cm (52.5 in.)
Net Weight (no fuel)	
	189 kg (415 lb) / 193 kg (423 lb)

53 cm (21 in.) cut and sewn seat with spring suspension provides a smooth comfortable ride on uneven terrain (Standard on the X580, X584, and X590).

Control console. Ergonomic design and color-coded for easy identification.

X590 Electronic throttle control. Instantly responds to deliver engine power and eliminate bogging down.

iTorque™ power system. Provides plenty of power and torque for excellent performance in any operating condition.



Four-wheel steering. All four wheels on the X584 steer the tractor for ultimate trimmability.

Hydraulic power steering. Makes 4-wheel steering even easier and provides excellent maneuverability. 30 cm (12 in.) uncut circle radius on the X584 with 54 in. mower. (Standard on the X584).

MulchControl™ Kit with One Touch Technology. Available with Accel Deep™ Mower Decks on Select Series Tractors.

DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources, and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.

ezyquiphire
Hire and Maintenance Specialists